

Storage / Compute Server: 2U8S16-4189A

2U 8x3.5" SATA, 16 DIMM 2x 10Gbit LAN, 6 PCIe M.2, Dual Ice Lake Xeon®



Key Features:

- 2U 8 x 3.5" NVMe U.2/ SAS/ SATA Hot Swap Drives
- Dual Socket P+ for 3rd Gen. Intel® Scalable Xeon® Processors
- 16 DDR4 up to 4TB 8-Channel Intel® Optane™ Memory
- 4 PCIe 4.0 x16 Slots, 2 PCIe 4.0 x8 Slots
- 1 M.2-2280/22110
- 2 10GbE LAN with IPMI 2.0
- 1200W Titanium Redundant Power Supply
- For Virtual Server, Compute Server, Database Server, Cloud

Specifications:

Processor

- Dual 3rd Generation Intel® Scalable Xeon® (Ice Lake Family)
- Socket P+ (LGA 4189), supports 270W, up to 40 Core 80 Threads

Chipset

- Intel® C621A

Memory

- 16 x DDR4 DIMM Sockets
- 8-channel memory bus per processor
- Supports up to 4TB ECC DDR4 3200MHz RDIMM
- Supports up to 4TB Intel® Optane™ Persistent Memory 200 series

Storage

- 8 x 3.5" NVMe U.2/ SAS*/ SATA Hot Swap Bays
- Intel® C621A 8 x SATA (6Gb/s) RAID-0/1/5/10
- 1 x M.2-2260/2280/22110 Socket NVMe/ SATA RAID-0/1
- Optional* Broadcom® 3108/3808/3816/3916 for SAS (12Gb/s)
- Optional Slim DVD drive bay
- 2 x SATA-DOM (Disk on Module)

Network

- 2 x 10GbE RJ45 LAN from Intel® X550 Controller
- RJ45 Gigabit LAN for IPMI 2.0 by AST2600 (KVM)
- Additional LAN or InfiniBand by PCIe add-on cards

Expansion Slot

- 4 x PCIe 4.0 x16 (Low Profile)
- 2 x PCIe 4.0 x8 (Low Profile)

Graphics

- Aspeed AST2600 BMC VGA (DB15)

Back I/O

- 2 x 10GbE RJ45 LAN, 1 x RJ45 IPMI
- 1 x DB15 VGA
- 4 x USB 3.0
- 1 x RS-232 COM

Internal I/O

- 3 x USB 3.0 (2 x Headers + 1 x Type A)
- 1 x TPM Header

Front I/O

- 2 x USB 2.0
- 1 x RS-232 COM

BIOS

- AMI®
- Watchdog Supported

Chassis

- 2U Rackmount with UID LED
- 3 x Cooling Fans
- Dimension: 3.5" (89 mm) H x 17.2" (437 mm) W x 25.5" (647 mm) D
- System Weight: 35.5 lbs. (16.1 kg) Net, 69 lbs. (31.2 kg) Gross

Power Supply

- 1200W (1+1) Redundant Titanium Level with PMBus
- 100-200Vac Input and 200-240Vdc Input

OS Supported

- Windows Server, Linux, FreeBSD, VMware

Applications

- Virtual Server, Compute Server, Database Server, Cloud Computing

Environments

- Operating Temperature: 10 to +35 C
- Non-operating Temperature: -40 to +60 C
- Vibration - Operating: 9.8 m/s²(1.0G) 5 to 500Hz
- Vibration - Non operating: 49 m/s²(5.0G) 15 to 500Hz
- Shock - Operating: 3,920 m/s² (400G) 2ms
- Shock - Non-Operating: 8,820 m/s² (900G) 1ms
- Operating Relative Humidity: 8% to 90% (non-condensing)
- Non-operating Relative Humidity: 5% to 95% (non-condensing)
- MTBF: 100,000 Hours
- FCC, CE, UL, RoHS Compliance