

2-Spindle, Intel, 15.4" W TFT, Thin & Light

Processor & Sockets	<ul style="list-style-type: none"> ■ Intel® Yonah & Pentium® M ◆ Intel Core Duo, 667MHz FSB, 2M L2 Cache, 1.66GHz (T1300) up to 2.16GHz (T1600) 		<ul style="list-style-type: none"> ■ 4 * USB 2.0 ports ■ 1 * TV-out S-Video ■ 1 * IEEE 1394 ■ 1 * Port Bar III 68-pin connector (Factory Option)
BIOS	<ul style="list-style-type: none"> ■ AMI BIOS code ■ 4Mb Flash EPROM ■ PMU, Plug & Play 		Keyboard (CBB) <ul style="list-style-type: none"> ■ 19 mm full size with MS-Windows function keys ■ 2.5mm travel
Chipset	<ul style="list-style-type: none"> ■ Intel 945GM + ICH7M 		Audio <ul style="list-style-type: none"> ■ Build in Azalia compliant audio chip ■ Build-in high-quality speakers ■ 2 * Internal Microphone
Main Memory	<ul style="list-style-type: none"> ■ 2 SO-DIMM socket for expansion up to 2048MB ■ DDRII 533/667 SDRAM 		Hot Keys (CBB) <ul style="list-style-type: none"> ■ Instant launch Keys <ul style="list-style-type: none"> ◆ 5 buttons: Power, Touchpad lock, email, internet, power 4 gear ■ Function Keys <ul style="list-style-type: none"> ◆ Fn+F1 suspend switch ◆ Fn+F2 Wireless Enable/Disable ◆ Fn + F3 LCD/CRT/LCD+CRT Switch ◆ Fn + F4 Brightness down ◆ Fn + F5 Brightness up ◆ Fn + F6 Mute ◆ Fn + F7 Volume Down ◆ Fn + F8 Volume Up
Display (CBB)	<ul style="list-style-type: none"> ■ 15.4" W active matrix color TFT ■ 15.4" WXGA, WSXGA+ 		Battery Pack & Life (CBB) <ul style="list-style-type: none"> ■ Primary: 6 cells, 2400mAh, 53Wh ■ Extended: 9 cells, 2400mAh, 80Wh ■ Smart battery, charging time, 4hrs/2.5hrs (System On/ Off) to 95%.
Graphics & Video Module	<ul style="list-style-type: none"> ■ Embedded Intel 945GM 		AC adapter (CBB) <ul style="list-style-type: none"> ■ Output: 19V DC, 3.42A, 65W ■ Input: 100~240V AC, 50/60Hz universal
CRT Display Modes	<ul style="list-style-type: none"> ■ VGA 640 x 480, 256/32K/64K/16.7M colors ■ SVGA 800 x 600 256/32K/64K/16.7M colors ■ XGA 1024 x 768 256/32K/64K/16.7M colors ■ SXGA 1280 x 1024 256/32K/64K/16.7M colors ■ UXGA 1600x1200 256/32K/64K/16.7M colors 		Pointing Device <ul style="list-style-type: none"> ■ Built-in Touch pad pointing device ■ 2 click buttons
Express Card Slot	<ul style="list-style-type: none"> ■ ExpressCard 34 / 54 support 		Thermal Solution <ul style="list-style-type: none"> ■ ADTD (Developed by Asus) to handle 35W CPU thermal envelope
Multi-Card Reader	<ul style="list-style-type: none"> ■ One built-in 4 in 1 card reader support ◆ MMC/ SD ◆ Memory Stick/ MS Pro 		Support OS <ul style="list-style-type: none"> ■ Windows XP Pro & Home edition ■ Windows Vista Capable PC
Hard Disk Drive (CBB)	<ul style="list-style-type: none"> ■ 2.5" 9.5 mm SATA/PATA HDD supported (Factory Option) ■ 60 / 80 / 100GB; support 4200/5400RPM 		Security <ul style="list-style-type: none"> ■ Pre-OS Authentication by programmable key code ■ BIOS Booting User Password Protection ■ HDD User Password Protection and Security Lock ■ Kensington Lock hole provided
Modem/FAX & LAN	<ul style="list-style-type: none"> ■ 10/100/1000 Mbps LAN built-in ■ Integrated V.92 MDC Fax/Modem w/ Azalia Ver 2.1 compliant 		Dimensions <ul style="list-style-type: none"> ■ 362 x 268 x 28.5 ~ 39mm (W x D x H, typical)
Optical Storage Device (CBB)	<ul style="list-style-type: none"> ■ 5.25" 12.7mm 8X/ 24X24X24X (max.) DVD combo drive ■ DVD Super Multi, 4x/2x, 2.4x/2.4x 		Weight <ul style="list-style-type: none"> ■ 2.9 kg (w/ 15.4" LCD, 9.5mm HDD, 8 x DVD-ROM and 6 cells Li-Ion battery pack)
LED Status Indicator	<ul style="list-style-type: none"> ■ Power-on/Suspend ■ Bat. Charging/full/low ■ Storage device access ■ Card Reader access ■ Bluetooth Indicator ■ Wireless indicator ■ Cap. Lock ■ Num Lock ■ Scroll Lock 		Wireless LAN <ul style="list-style-type: none"> ■ Built-in antenna ■ Intel Golan 802.11a/b/g support ■ ASUS module (TBD)
Interface	<ul style="list-style-type: none"> ■ 1 * D-sub VGA port ■ 1 * S/PIDF jack ■ 1 * Microphone-in jack ■ 1 * RJ11 Modem jack for phone line ■ 1 * RJ45 LAN Jack for LAN insert 		Bluetooth <ul style="list-style-type: none"> ■ Option
			Factory option: <ul style="list-style-type: none"> ■ TPM 1.2 ■ 1.3M pixel CMOS Camera (on B-part) with indication LED (green color)