



V4100 4 LAN MB Specification

		 
Processor		VIA Eden-V4 400MHz~1GHz low power processors FSB 400/533MHz (fanless)
Chipset		VIA CN700 + VT8237R Chipset
Memory		1x DDR2 SO-DIMM, up to 1GB
LAN		4x Realtek 10/100 Base-T Ethernet
Audio		Onboard buzzer only
Graphic		CN700 built-in 128-bit Unichrome Pro 3D/2D VGA controller CRT output (pin header)
Storage Interface		1x 44-pin PATA connectors(Up to ATA133) 1x SATA connector(Supports 2 ports (with RAID0/1 on 1 port)) 1x Compact Flash socket
I/O	Rear IO Connectors	4x RJ-45 connector 2x USB 2.0 ports 1x 5V DC in jack 1x Serial Port (Com1 port)
	Onboard IO Connectors	1x Mini-PCI slot 1x parallel ports pin header support SPP/EPP/ECP (printer port) 1x RS-232 pin header(COM2 port) 1x 16-pin header for CRT VGA 1x 10-pin header for PS/2 KB/Mouse 1x pin header for USB 4x green/yellow stack LED for LAN status(Green for 10/100 LAN speed, 10 off, 100 on)(Yellow for LAN Active/Link) 1x green LED for power status 2x green and 1x red LED stack for GPO status 2x fan headers
Others		Optional Hardware LAN Bypass Function on ETH 0 & 1(LAN 1, 2) Bypass Ethernet ports when system fault automatically
Dimension	Size	203mm x 146mm