



MODEL	Poly 940X6 Dual Xeon Motherboard
Processor	Dual Intel® Xeon processors up to 2.80 GHz+
Chipset	Intel® E7505
Form Factor	Extended ATX 12" x 13"
Recommended Chassis	2U: SC822 4U/Tower: SC842, SC742, SC760P4, SC762, SC830P4, SC850P4
System Bus	533/400 MHz
Memory Capacity & Slots	12 GB ECC Reg. DDR 266/200 SDRAM in 6 DIMMs * 2-way interleaved memory
Expansion Slots	1 8xAGP Pro 1.5V, 1 64-bit PCI-X 133MHz, 2 64-bit PCI-X 100MHz, 2 32-bit PCI
Onboard SCSI/RAID	Adaptec® 7902W dual channel Ultra320 SCSI
ZCR Support	Zero channel RAID
Onboard LAN	Intel® 82545EM Gigabit Ethernet
Onboard Audio	AC'97 Audio CODEC
Built-in EIDE	ATA/100
USB	USB 2.0 w/Up to 6 USB ports for a maximum speed of up to 480Mbps
Other Onboard I/O Devices	1 floppy port 2 fast UART 16550 serial ports 1 ECP/EPP parallel port PS/2 mouse and keyboard conn.
Manageability	Watch Dog, Docto●II
PC Health Monitoring	Monitors CPU voltages, +1.8V, +3.3V, +5V, ±12V & +3.3V standby and 3-fan status, supports system mangement utility, chassis intrusion header
Thermal Control	Overheat LED indication, thermal control tachometer, fan connectors
Other Features	ACPI/APM power management, internal/external modem ring-on, WOL, control of power-on mode for recovery from AC power loss, STR (Suspend-To-RAM), chipkill support, CPU thermal trip support for processor protection
BIOS	Phoenix 4 Mb Flash ROM