

Small Form Factor Storage

Think Big. Go Small. Eco-Smart Computing



Model: MiniStor 860N10 Small and quiet, energy saving High performance, affordable price



Featured Highlights

- Data file sharing among Windows, Linux OS, and Macintosh users, with user name, password protection, and managed access in local workgroups.
- The backup and recovery application provides system backup, remote boot and recovery for Windows clients.
- Can act as a Dynamic Host Configuration Protocol (DHCP) server.
- Can also act as a DHCP client.
- Can be used as linear storage or be set up as RAID 0, 1, 5, 6, 10, 50.
- User-friendly Web interface for setting up users and access rights.
- Built-in FTP server provides convenient high-speed file transfers.

Specifications

<p>Processor</p> <ul style="list-style-type: none"> • 2.4GHz Dual Core 	<p>USB</p> <ul style="list-style-type: none"> • 4x USB 2.0 connectors
<p>Flash</p> <ul style="list-style-type: none"> • 2GB with NAS and OS (Optional MS HomeServer, MS Storage) 	<p>OS Support:</p> <ul style="list-style-type: none"> • Operating System: Linux/FreeBSD, (Optional Microsoft Home Server)
<p>LAN</p> <ul style="list-style-type: none"> • 2x Gigabit LAN port 	<p>Application:</p> <ul style="list-style-type: none"> • Entertainment, Graphics Terminal, Digital Signage, Kiosk, Vehicle/ Boat PC, Settop box, Surveillance, Appliance, PBX.
<p>Main Memory</p> <ul style="list-style-type: none"> • DDR3 4GB • Optional: up to 8GB system memory 	<p>Chassis</p> <ul style="list-style-type: none"> • 205(W) x 286(H) x 205(D)mm • 8.1(W) x 11.25(H) x 8.1(D)inch • 270W Power
<p>Network</p> <ul style="list-style-type: none"> • DHCP client/server • Network Protocol: CIFS/SMB, NFS, FTP • iSCSI (optional), can be configured as mix with NAS and iSCSI 	<p>Certification</p> <ul style="list-style-type: none"> • system: FCC, CE • AC Adapter: FCC, CE, UL
<p>Expansion Slots</p> <ul style="list-style-type: none"> • 1 PCI Express 3.0 16x connector 	<p>Environment</p> <ul style="list-style-type: none"> • Operating Temperature: 0 to +55 C° • Shock:- 3,920 m/s² (400G) 2ms • Vibration: 9.8 m/s²(1.0G) 5 to 500Hz • Noisy Rating: 28-38 db
<p>Storage</p> <ul style="list-style-type: none"> • 10x 3.5" SATA-II/SATA-6G/s Hot-Swap Drive 3.0TB or 4.0TB • RAID 5, 6, 10, 1 and 0 with Hot Spare supported 	

Polywell Computers, Inc. 1461-2 San Mateo Ave. South San Francisco, CA 94080 www.polywell.com